



## Reducering Polyamid RAL 7035 PG - PG

### Spesifikasjon

MATERIALE	Polyamid PA6 glasfiberforsterket
TEMPERATUROMRÅDE	-30°C...+100°C
FARGE	Lysgrå RAL 7035
HALOGENFRI	Ja

## Varianter

EL-NUMMER	YTTERGJENGE	INNERGJENGE	L MM	T_MM	D MM	H MM	SW MM	E MM	ANTALL/PKN
1242300	PG9/15,2	PG7/12,5	8	9,5	7	20,5	19	20.7	100
1242301	PG11/18,6	PG7/12,5	8	9	7,5	14	22	24	100
1242302	PG11/18,6	PG9/15,2	8	11	10	22	22	24.8	100
1242303	PG13,5/20,4	PG7/12,5	9	9,5	7,5	15	24	26	100
1242304	PG13,5/20,4	PG9/15,2	9	9	10	15	24	26	100
1242305	PG13,5/20,4	PG11/18,6	9	12	11,5	24	24	26	100
1242306	PG16/22,5	PG9/15,2	10	10	10	16	27	29	100
1242307	PG16/22,5	PG11/18,6	10	9	11,5	16	27	29	100
1242308	PG16/22,5	PG13,5/20,4	10	13,5	13	27	27	29	100
1242309	PG21/28,3	PG11/18,6	11	10,5	11,5	16	32	35.5	100
1242310	PG21/28,3	PG13,5/20,4	11	10,5	13,5	16	32	35.5	100
1242311	PG21/28,3	PG16/22,5	11	11	15,5	16	32	35.5	100
1242312	PG29/37,0	PG13,5/20,4	11	12,5	14	17	40	43	50
1242313	PG29/37,0	PG16/22,5	11	12,5	17	17	40	43	50
1242314	PG29/37,0	PG21/28,3	11	13	22	17	40	43	50
1242316	PG36/47,0	PG21/28,3	13	13	21,5	19	50	54	50
1242317	PG36/47,0	PG29/37,0	18	18,5	30,5	24	50	54	50
1242318	PG42/54,0	PG21/28,3	18	12,5	21,5	24	55	60	25
1242319	PG42/54,0	PG29/37,0	18	18,5	28	24	55	60	25
1242320	PG42/54,0	PG36/47,0	18	18	39	24	55	60	25
1242321	PG48/59,3	PG29/37,0	18	17,5	30,5	24	60	65	25
1242322	PG48/59,3	PG36/47,0	14	16	38,5	20	60	65	25
1242323	PG48/59,3	PG42/54,0	17	18,5	42,5	23	60	65	25